



C1 0.6/1kV Heat Shrink Cable Accessories

Introduction

Single core, 2 cores, 3 cores, 4 cores and 5 cores cable accessories. Suitable for protection of indoor and outdoor electric power cable joint and termination up to 1kV.

Features

- Voltage class: 0.6kV/1kV
- Operating temperature: -55 to 105°C
- Supplied by set, with the materials in the kit
- Well resistance against weather and damage

Dimension

Termination		Joint		Size for conductor mm ²
Part No. C1	Cable core number	Part No. C1	Cable core number	
NSY-1100	1	JSY-1100	1	4-6
NSY-110	1	JSY-110	1	10-16
NSY-111	1	JSY-111	1	25-50
NSY-112	1	JSY-112	1	70-120
NSY-113	1	JSY-113	1	150-240
NSY-114	1	JSY-114	1	300-400
NSY-1200	2	JSY-1200	2	4-6
NSY-120	2	JSY-120	2	10-16
NSY-121	2	JSY-121	2	25-50
NSY-122	2	JSY-122	2	70-120
NSY-123	2	JSY-123	2	150-240
NSY-124	2	JSY-124	2	300-400
NSY-1300	3	JSY-1300	3	4-6
NSY-130	3	JSY-130	3	10-16
NSY-131	3	JSY-131	3	25-50
NSY-132	3	JSY-132	3	70-120
NSY-133	3	JSY-133	3	150-240
NSY-134	3	JSY-134	3	300-400
NSY-1400	4	JSY-1400	4	4-6
NSY-140	4	JSY-140	4	10-16
NSY-141	4	JSY-141	4	25-50
NSY-142	4	JSY-142	4	70-120
NSY-143	4	JSY-143	4	150-240
NSY-144	4	JSY-144	4	300-400
NSY-1500	5	JSY-1500	5	4-6
NSY-150	5	JSY-150	5	10-16
NSY-151	5	JSY-151	5	25-50
NSY-152	5	JSY-152	5	70-120
NSY-153	5	JSY-153	5	150-240
NSY-154	5	JSY-154	5	300-400

Technical Data

Property	检测方法	要求
Work frequency voltage withstand	4 kV/ 1 min.	No breakdown, no flashover
Load cycling (3 times)	5 hrs heating*	2.4 kV/ 4 hrs
	3 hrs cooling	No breakdown, no flashover
Work frequency voltage withstand	2.4 kV/ 4 hrs	No breakdown, no flashover

Note: * Conductor temperature 75°C